

# MAL403 series


## AIR UNIT (L.UNIT)



### Specification

| Model                       | MAL403                  |          |          |
|-----------------------------|-------------------------|----------|----------|
| Bore No.                    | 8A                      | 10A      | 15A      |
| Port size                   | 1/4                     | 3/8      | 1/2      |
| Medium                      | Air                     |          |          |
| Max. operating pressure     | 1 MPa                   |          |          |
| Proof pressure              | 1.5 MPa                 |          |          |
| Ambient temperature         | - 5~+60°C (No freezing) |          |          |
| Lubricating oil capacity    | 200 c.c                 |          |          |
| Min. Flow for oil drip      | 30 ℓ/min                | 65 ℓ/min | 80 ℓ/min |
| Recommended lubricating oil | Turbine oil ISO-VG32    |          |          |
| Weight                      | 410 g                   |          |          |

### Symbol



### Order example

MAL403 - 8A - □□ - B - □

MODEL

PORT SIZE

8A: 1/4  
10A: 3/8  
15A: 1/2

BOWL  
Blank: PC bowl  
N: Nylon bowl

FLOW DIRECTION

Blank: Left to right  
R: Right to left

PORT THREAD

Blank: Rc thread  
G: G thread  
NPT: NPT thread

Blank: Without bracket  
B: C type bracket

### Option accessories

#### C type bracket

